



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :

B05B 3/04, 3/16, A01G 25/00

A1

(11) International Publication Number:

WO 00/48741

(43) International Publication Date:

24 August 2000 (24.08.00)

(21) International Application Number:

PCT/IB00/00162

(22) International Filing Date:

16 February 2000 (16.02.00)

(30) Priority Data:

VI99A000030

16 February 1999 (16.02.99)

IT

(71)(72) Applicant and Inventor: DRECHSEL, Arno [IT/IT]; Via Castel Mareccio, 4, I-39100 Bolzano (IT).

(74) Agent: MAROSCIA, Antonio; Maroscia & Associati S.r.l., Corso Palladio, 42, I-36100 Vicenza (IT).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: SELF-ADJUSTING ROTATING JOINT, ESPECIALLY FOR LIQUID DISTRIBUTION DEVICES

(57) Abstract

A self-adjusting rotating joint (1), especially for liquid distribution devices, including a first substantially tubular element (3), adapted to be connected to a liquid feeding inlet pipe, a second substantially tubular element (2), adapted to be connected to a liquid distribution nozzle, connecting means (6, 25) adapted to connect pivotally first (3) and second element (2), so as to allow their reciprocal rotation around a common axis (V), with limited axial relative displacement, transmitting a reaction force generated by the jet and lying on a plane passing through said common axis (V), braking means (15, 16, 17, 18, 20, 21, 22, 23, 30, 31) to counter the relative rotary motion of the element (2,3) about the rotation axis (V). The rotating joint is characterised in that the connecting means are made of a substantially cylindrical tubular element (6, 25) with substantially constant outer diameter.

